


## **SHIN YOUNG**

**Light Construction Equip** 

we are doing our best to study and develop several kinds of equipment by ourselves in order to meet with customer's various needs.





## SHIN YOUNG Table Of Contents

03.	ABOL	JT	SHIN	YOL	JNG

- 04. CONCRETE VIBRATOR ACTION UNIT
- 05. PLATE COMPACTOR
- 06. CONCRETE VIBRATOR DRIVE UNIT
- 07. CONCRETE VIBRATOR MOTOR UNIT HANDY & FOAM VIBRATOR
- 08. SUBMERSIBLE PUMP
- 09. HANDY REBAR CUTTER
- 10. PORTABLE REBAR BENDER
- 11. MOBILE REBAR CUTTER ROAD CUTTER





We continue to develop and extend the business scopes since foundation in 1986,
We manufacture and produce the small-sized construction equipment such as Concrete Vibrator, Flexible Pump, Plate Compactor,
Portable Rebar Bender and export to overseas

Also, we are doing our best to study and develop several kinds of equipment by ourselves in order to meet with customer's various needs.

We once again thank you for you and will always try our best to serve and support you.

Thank you and Best regards.

All Sin Young IND. CO, employees

## CONCRETE VIBRATOR ACTION UNIT


SYV series concrete vibrator provides the best performance & dynamic power by special vibration system of pendulum type. The low rotational speed about 3.000 RPM provides less wear & tear for all rotating parts. Unique spring concept guarantees long durability.

Available to our drive unit and most of the standard drive units Spring connection (Premium), Direct connection (Standard)





| Standard Carton |







| Standard |

| Premium |

Model	Dia X L (mm)	Frequency (V. P. M)	Revolution (R. P. M)	Flexible Hose	Weight (kg)	Engine unit
SYV-32	32 x 445		3.000 ~3.600		15	
SYV-38	38 x 445	12.000		6M	16	3.5~6HP 3.600RPM
SYV-45	45 x 445	~ 14.000		(Standard)	17	Gasoline
SYV-60	60 x 545				24	

## PLATE COMPACTOR

Single-direction plate compactor is designed to compact granular soil and crushed aggregate. Aluminum pulley & rotor user friendly compactors.



Model: SYC-120

Model	Plate Size L x W(m)	VPM	Travel Speed (m/min)	Centrifugal Force (kgt)	Weight (kg)	Engine HP	Fuel
SYC-60	510 x 350	5600	20~25	1,030	60	4.5~5.5 HP	Gasoline
SYC-80	550 x 420	5800	20~25	1,550	70	5.5~6 HP	Gasoline
SYC-120	600 x 480	5800	20~25	2,100	115	5.5~6 HP	Gasoline

## CONCRETE VIBRATOR DRIVE UNIT

The strong and compact 4 cycle engine & frame are designed to drive all size of vibrators.



I Engine Frame I EFS I



| Engine Frame | EFT |



I Dynapac Engine Coupling I



I Ball Engine Coupling I



I Pin Engine Coupling I



I Dynapac Engine Shaft I




I Ball Engine Shaft I



I Drive Unit & Action Unit I

# CONCRETE VIBRATOR MOTOR UNIT HANDY & FOAM VIBRATOR

SYEM series electric vibrator motor gives users a easy solution of power nuit. SYHV of handy vibrator is more useful & practical in small space.



#### Specification

Model	Frequency(V. P. M)	Amplitude(mm)	Head Dia X L(mm)	Total Length(m)	Weight(kg)	Power(w)
SYHV-32	12.000	1.1	32 X 190	1.2	5	480

#### Specification ...

Model	Output (kw)	Motor Speed (RPM/Hz)	Volfage (v)	Weight (kg)	Remark	Available Action Unit
SYEM-1	0.75(1HP)			14.3	1 phase	SYV-32, 38, 45
SYEM-2	1.50(2HP)	2.850/50 3.450/60	110	18	2 phase	SYV-60
SYEM-3	2.20(3HP)	3.450/60	220	25	3 phase	SYV-60



## SUBMERSIBLE PUMP



SYSP submersible pump is suitable for drainage disposal work. Muddy water can also be pumped out easily. Including flexble hose & body. No priming required.



Model: SYSP-3M

Model	Discharge Dia. (inch)	Max. Lift (m)	Max. Capacity ( /min)	Hose Length (m)	Weight (kg)	Engine HP/RPM(max)
YSP-3M	3	21	1.500	Standard: 6M	22	3.5~6HP.3.600RPM

## HANDY REBAR CUTTER

Lightest but durable, efficient & faithful performance in its duty.
H-25C is applicable to light, heavy-duty & repairing job in the site.
Ships complete in a steel carrying cafe with hydraculic oil, a tool kit and extra blades.



Model: SYC-25



#### Specification

Model	Max cut diameter	Cut speed	Power	Tool Wight	Dimensions (L x W x H)
SYC-25	25mm	3 Seconds	22V, 50/60hz, 1phase	21kg	130 x 250 x 480


#### **Cutting Performance**

Model / Bar (mm)	D10	D13	D 16	D 19	D 22	D 25	D 32
SYC-25	4	2	1	1	i	1	0



### PORTABLE REBAR BENDER

It is designed for portable by two persons and accurate bending consistently. Strong mechanical bender with two preset angle locks helps to save valuable man hours. It is very simple and safe to operate with effective performance.







Model: SY-35S

#### Specification

Model	Max Bending diameter	Bending speed	Power	Tool weight	Dimensions (L x W x H)
SY-25S	25mm	4 Seconds	220V, 50/60hz, 1phase	92kg	450 X 410 X 530
SY-35S	35mm	4 Seconds	220V, 50/60hz, 1phase	158kg	604 X 510 X 610

#### **Bending Performance**

Model / Bar (mm)	D 10	D 13	D16	D 19	D 22	D 25	D 35
SY-25S	4	2	1	1	1	1	0
SY-35S	5	4	3	2	1	1	1

#### Roller Component

SY-25S / Bar(mm)	D 10 ~ 13	D 16 ~ 19	D 22 ~ 25
Max. Bar	. 4	2	. 1
Center Roller	Stirrup	Ø70	Ø70
Rotating Roller	Ø 95	Ø95	Ø80

SY-35S / Bar(mm)	D 10 ~ 13	D 16 ~ 19	D 22 ~ 25
Max. Bar	4	2	1
Center Roller	Stirrup	Ø68	Ø108
Rotating Roller	Ø148	Ø148	Ø100

### MOBILE REBAR CUTTER

The performance is more stable with compact structure and strong technical force. Durable wheels make it easy to move where it is needed.

Easy operation, high efficiency make it more convenient and economical.







#### Specification

Model	Max Cut diameter	Cut speed	Power	Tool weight	Dimensions (L x W x H)	
SYW-25	25mm	1 Seconds	220V, 50/60hz, 1phase	160kg	850 X 530 X 750	
SYW-35	35mm	1 Seconds	220V, 50/60hz, 1phase	280kg	1100 X 560 X 1020	

#### **Cutting Performance**

Model / Bar (mm)	D 10	D13	D 16	D 19	D 22	D 25	D 32
SYW-25	4	3	2	1	1	1	0
SYW-35	7	5	3	3	3	1	1

## **ROAD CUTTER**

Model	Dimension L x W x H(m)	Cutting Depth Max. (mm)	Water Tank()	Weight (kg)	Engine HP	Fuel
SYCC-16	1,260 x 60 x 1,020	120~180	39	150	13~20HP	Gasoline





we are doing our best to study and develop several kinds of equipment by ourselves in order to meet with customer's various needs.

766-2, Haseong-ro, Haseong-myeon, Gimpo-si, Gyeonggi-do, Republic of Korea

82-31-981-6588



82-31-981-7110

sinyoung5986@naver.com (🖂)

shinyoungmc.com (\*)